

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 May 2004 (13.05.2004)


PCT

(10) International Publication Number
WO 2004/040900 A3

- (51) International Patent Classification⁷: **H04N 7/18**
- (21) International Application Number: **PCT/US2003/034190**
- (22) International Filing Date: 28 October 2003 (28.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/421,831 28 October 2002 (28.10.2002) US
- (71) Applicant (for all designated States except US): **ELNICKY ENTERPRISES INC.** [US/US]; 4278 Rouge Circle, Troy, MI 48098 (US).
- (72) Inventor; and
(75) Inventor/Applicant (for US only): **ELNICKY, Robert, N.** [US/US]; 4278 Rouge Circle, Troy, MI 48098 (US).
- (74) Agent: **DEGRAZIA, Gregory, D.**; Howard & Howard Attorneys, P.C., 39400 Woodward Avenue, Suite 101, Bloomfield Hills, MI 48304 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: CAMERA SUPPORT ARM



(57) **Abstract:** An assembly for mounting a remotely controlled camera (14) includes a frame affixed to a mounting surface for supporting the camera. A first member (32) is rotationally mounted to the frame (24) defining a first axis of rotation. A second member (34) is rotationally mounted to the first member (32) defining a second axis of rotation (36) intersecting the first axis of rotation. The camera (14) is rotationally mounted to the second member (34) at a location spaced from the second axis of rotation (36) so that the camera rotates around at least a third axis and a fourth axis relative to the second member.

WO 2004/040900 A3